



HIPER HR
MULTI-PURPOSE
GNSS RECEIVER





Modern Hybrid of Positioning Technology

- Compact, lightweight, rugged design – Capable of withstanding a 2 meter pole drop
- Five unique data communication options
- All signals, all satellites, all constellations
- Field tested, field ready IP67 design
- Compact form factor ideal for Millimeter GPS and Hybrid Positioning
- Revolutionary 9-axis IMU and ultra-compact 3-axis eCompass

Better things in smaller packages

The HiPer HR is smaller and lighter, but don't let its small size fool you. It's not only packed with the most advanced GNSS technology, it is also built to withstand the harshest field environments. The HiPer HR is built with a rugged aluminum-alloy housing, not weak plastic, so it can take the punishment of the job site.

Using the Topcon advanced GNSS chipset with Universal Tracking Channels™ technology, the receiver automatically tracks each and every satellite signal above - now and into the future.

All signals, all satellites, all constellations — all in a compact, rugged design, with an integrated IMU and eCompass.



IP67 Waterproof Rating

TILT™- Topcon Integrated Leveling Technology


The HiPer HR incorporates a revolutionary 9-axis Inertial Measuring Unit (IMU) and an ultra-compact 3-axis eCompass. This advanced technology compensates for mis-leveled field measurements out of plumb by as much as 15°.

Awkward shots on steep slopes or hard to reach spots are now a breeze with TILT™.





GNSS Tracking	
Number of Channels	452 with patented Universal Tracking Channel Technology
GPS	L1 C/A, L1C, L1P(Y), L2P(Y), L2C, L5
GLONASS	L1 C/A, L1P, L2 C/A, L2P, L3C
Galileo	E1, E5a, E5b, E5AltBOC, E6
BeiDou	B1, B2, B3 with ICD availability
IRNSS	SPS-L5
SBAS	WAAS/EGNOS/MSAS
QZSS	L1 C/A, L1C, L2C, L5, LEX
L-band	1525-1560 MHz
Satellites Tracked	All in view
Accuracy	
(L1 + L2)	H: 3.0 mm + 0.3 ppm V: 5.0 mm + 0.5 ppm
Precision Static**	H: 3.0 mm + 0.1 ppm V: 3.5 mm + 0.4 ppm
RTK	H: 5 mm + 0.5 ppm V: 10 mm + 0.8 ppm
Data Update / Output Rate	Up to 20 Hz
Communication	
Additional Communications	Wi-Fi Bluetooth® LongLink™
Data and Memory	
Real Time Data Output	TPS, RTCM SC104 v2.x, 3.x, CMR/CMR+, RINEX
NMEA 0183 Output	Version 2.x, 3.x and 4.x
On-board Memory	8GB Internal
Power	
Power Source	External power 6 to 28 VDC 1x internal battery (3.7 V, 5200 mAh) 1x removable battery (7.2 V, 2900 mAh)
Operating Time	Up to 9 hours with included batteries
Environmental and Physical	
Dimensions (w x h)	115 x 132 mm
Operating Temp.	-40°C to 80°C
Water/Dust Rating	IP67
Drop and Topple	2 meter pole-drop
Weight	1.172 g (including internal and hot swappable external batteries)



Form and Function

The most advanced GNSS technology available, yet compact enough to fit in the palm of your hand.

Highly configurable

Designed to grow with you, unique electronic option files empower you to activate available features instantly – increasing functionality as project demands expand.

Software

MAGNET software is tailored for use with Topcon GNSS receivers in both field and office functions.

MAGNET Field

MAGNET Field software increase your productivity and connect you to others in the field as well as in the office.

Features

Cloud connected data exchange and backup, Data Collection, StakeOut, Real Time Roads, Calculate Areas & Volume, DTM, Generate Contour and more.

MAGNET Enterprise

A managers dream of tracking all field and office data in one simple to access web interface. Store and exchange your field data in the Enterprise cloud. Save the drive time by sending your field and office updates to the cloud rather than driving back to the office.

MAGNET Office

Full CAD functionality with MAGNET Office Site and Topo. Or field data processing with MAGNET Office Tools inside AutoCAD® products, like Civil3D®. The MAGNET Office solution module that best fits your needs.

** Under nominal observing conditions and strict processing methods, including use of dual frequency GPS, precise ephemerides, calm ionospheric conditions, approved antenna calibration, unobstructed visibility above 10 degrees and an observation duration of at least 3 hours (dependent on baseline length).



For more information:
topconpositioning.com/hiper-hr

Specifications subject to change without notice.
©2017 Topcon Corporation All rights reserved.
7010-2199 B 3/17

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.

